WHAT WE CLAIM IS:

Sub Al > 1

A fuel blend for use in an internal combustion engine, the fuel blend comprising: hydrocarbon-containing fuel component;

an oxygen-containing component capable of providing oxygen for combustion of the fuel component under conditions prevailing during the combustion cycle of the internal combustion engine;

wherein the major oxygen-providing agent of the oxygen-containing component is one or more compounds having the general formula (I):

10

$$R_2 - Q - (CO) - R_1 \tag{I}$$

wherein R₁ is selected from hydrogen, lower alkyl, lower alkenyl and lower alkynyl groups;

15 15 15

R₂ is selected from lower alkyl, lower alkenyl and lower alkynyl groups, or a group having the general formula (II):

$$R_3 - (CO) - O - R_4$$
 (II)

20

wherein R₃ is selected from lower alkyl, lower alkenyl and lower alkynyl groups; and

R₄ is selected from lower alkyl groups.

25

2. A fuel blend as claimed in claim 1, wherein R₁ is selected from hydrogen, C₁ or C₂ alkyl, C₂ alkenyl and C₂ alkynyl groups.

Suly

3. A fuel blend as claimed in claim 2, wherein R₁ is selected from hydrogen, C₁ or C₂ alkyl.

A fuel blend as claimed in claim 3, wherein R₁ is methyl. 4. A fuel blend as claimed in claim 3, wherein R₁ is ethyl. 5. A fuel blend as claimed in claim 1, wherein R2 is selected from C1 to C4 alkyl, C2 5 6. alkenyl and C2 alkynyl groups. A fuel blend as claimed in claim 6, wherein R₂ is C₁ or C₂ alkyl. 7. 10 8. A fuel blend as claimed in claim 7, wherein R₂ is methyl. 9. A fuel blend as claimed in claim 7, wherein R₂ is ethyl. A fuel blend as claimed in claim 1, wherein the compound of general formula (I) 10. 15 is methyl acetate. A fuel blend as claimed in claim 1, wherein the compound of general formula (I) 11. is ethyl acetate. A fuel blend as claimed in claim 1, wherein the compound of general formula (I) is methyl formate. A fuel blend as claimed in claim 1 wherein the compound of general formula (1) 13. is ethyl formate. 25 A fuel blend as claimed in claim 1 wherein the compound of general formula (I) 14. is tertiary butyl acetate.

Subr


- 15. A fuel blend as claimed in claim 1, wherein R_2 is a group of general formula (II), in which R_3 is a C_1 to C_4 alkyl.
- 16. A fuel blend as claimed in claim 5, wherein R₄ is a C₁ to C₄ alkyl.

17. A fuel blend as claimed in claim 14, wherein R_3 and R_4 are each independently selected from C_1 or C_2 alkyl.

- 18. A fuel blend as claimed in claim 1 in which the compound of general formula (I) is ethylene glycol diacetate.
 - 19. A fuel blend as claimed in claim 1, wherein the hydrocarbon-containing fuel component is selected from the group consisting of diesel and gasoline.
- 20. A fuel blend as claimed in claim 1, wherein the major oxygen-providing component comprises a first compound of formula (I), in which R₂ is ethyl, and a second compound of formula (I), in which R₂ is methyl.
 - 21. A fuel blend as claimed in claim 20, wherein both the first and second compounds are compounds in which R_1 is a C_1 to C_4 alkyl.
 - 22. A fuel blend as claimed in claim 21, wherein the first compound and the second compound are present in a ratio of from 1:5 to 5:1.
 - 23. A fuel blend as claimed in claim 21, wherein the first compound and the second compound are present in a ratio of from 1:1 to 1:1.5.
 - 24. A fuel blend as claimed in claim 23, wherein the first compound is methyl acetate and the second compound is ethyl acetate.

20

- 25. A fuel blend as claimed in claim 1, wherein the major oxygen-providing component comprises a first compound of formula (I), in which R₂ is a group of general formula (II), and a second compound of formula (I), in which R₂ is a C₁ to C₄ alkyl.
- 26. A fuel blend as claimed in claim 25, wherein the first compound is a compound in which R₁ is a C₁ to C₄ alkyl.
- 27. A fuel blend as claimed in claim 26, wherein the second compound is a compound in which R_1 is a C_1 to C_4 alkyl.
- 28. A fuel blend as claimed in claim 27, wherein the first compound is ethylene glycol diacetate.
- 15 29. A fuel blend as claimed in claim 28, wherein the second compound is selected from methyl acetate, ethyl acetate and mixtures thereof.
 - 30. A fuel blend as claimed in claim 25, wherein the first compound and second compound are present in a ratio of from 0.5:1 to 10:1.
 - 31. A fuel blend as claimed in claim 30, wherein the first compound and second compound are present in a ratio of from 1:1 to 5:1.
 - 32. A fuel blend as claimed in claim 1, further comprising a stabilizer.
 - 33. A fuel blend as claimed in claim 32, wherein the stabilizer is selected from alcohols having from 1 to 8 carbon atoms.



The state of the s

20

34. A fuel blend as claimed in claim 33, wherein the stabilizer is selected from alcohols having from 2 to 5 carbon atoms.

- 35. A fuel blend as claimed in claim 34, wherein the stabilizer is ethanol.
- 36. A fuel blend as claimed in claim 32, wherein the compound of general formula (I) and the stabilizer are present in a ratio of from 20:1 to 150:1.
- 37. A fuel blend as claimed in claim 36, wherein the compound of general formula (I) and the stabilizer are present in a ratio of from 75:1 to 125:1.
 - 38. A fuel blend as claimed in claim 1, further comprising an alcohol having from 2 to 5 carbon atoms and bearing one or more alkyl substituents.
- 39. A fuel blend as claimed in claim 38, wherein the alcohol is an alkyl substituted butyl alcohol.
 - 40. A fuel blend as claimed in claim 39, wherein the alcohol is tertiary butyl alcohol.
 - 41. A fuel blend as claimed in claim 38, wherein the alcohol and the compound of general formula (I) are present in a ratio of from 1:0.6 to 1:5.
 - 42. A fuel blend as claimed in claim 1, further comprising a biocide.
 - 43. A fuel blend as claimed in claim 1, wherein the hydrocarbon-containing fuel component is gasoline and the compound of general formula (I) is present in an amount sufficient to provide an oxygen-content in the fuel blend of 1 to 5 percent by weight.

Sul 25

- 44. A fuel blend as claimed in claim I, wherein the hydrocarbon-containing fuel component is diesel and the compound of general formula (I) is present in an amount sufficient to provide an oxygen-content in the fuel blend of 1 to 10 percent by weight.
- An oxygenating additive for a hydrocarbon-containing fuel comprising: a first compound having a general formula (III):

$$R_7 - (CO) - O - R_6 - O - (CO) - R_5$$
 (III)

wherein R₅ is selected from lower alkyl, lower alkenyl and lower alkynyl groups; R₆ is selected from lower alkyl; and

wherein R₇ is selected from lower alkyl, lower alkenyl and lower alkynyl groups;

a second compound having a general formula (IV):

$$R_9 - O - (CO) - R_8$$
 (IV)

wherein R₈ is selected from hydrogen, lower alkyl, lower alkenyl and lower alkynyl groups; and

R₉ is selected from lower alky, lower alkenyl and lower alkynyl groups.

- 46. An oxygenating additive as claimed in claim 45, wherein R₅ is selected from C₁ to C₄ alkyl.
- 25 47. An oxygenating additive as claimed in claim 46, wherein R₅ is methyl.
 - 48. An oxygenating additive as claimed in claim 45, wherein R₆ is ethyl.

and

Then the time in the time that the time

10

- 49. An oxygenating additive as claimed in claim 45, wherein R₇ is selected from C₁ to C₄ alkyl.
- 50. An oxygenating additive as claimed in claim 49, wherein R₇ is methyl.
- 51. An oxygenating additive as claimed in claim 45, wherein the compound of general formula (III) is ethylene glycol diacetate.
- 52. An oxygenating additive as claimed in claim 45, wherein R₈ is selected from hydrogen, and C₁ to C₄ alkyl.
 - 53. An oxygenating additive as claimed in claim 52, wherein R₈ is methyl.
- 54. An oxygenating additive as claimed in claim 45, wherein R₉ is selected from C₁ to C₄ alkyl.
- 55. An oxygenating additive as claimed in claim 54, wherein R₉ is selected from methyl and ethyl.
- 20 56. An oxygenating additive as claimed in claim 45, wherein the compound of general formula (IV) is selected from methyl acetate and ethyl acetate and mixtures thereof.
- 57. An oxygenating additive as claimed in claim 45, wherein the compound of general formula (III) and the compound of general formula (IV) are present in a ratio of from 0.5:1 to 5:1.

15

20

- 58. An oxygenating additive as claimed in claim 57, wherein the compound of general formula (III) and the compound of general formula (IV) are present in a ratio of from 1:1 to 2.5:1.
- 59. An oxygenating additive as claimed in claim 45, further comprising a biocide.
- 60. An oxygenating additive as claimed in claim 45, further comprising a stabilizer.
- 61. An oxygenating additive as claimed in claim 60, wherein the stabilizer is selected from alcohols having from 2 to 5 carbon aroms.
 - 62. An oxygenating additive as claimed in claim 61, wherein the stabilizer is ethanol.
 - 63. An oxygenating additive as claimed in claim 60, wherein the ratio of the combined amounts of the compounds of general formulae (III) and (IV) to the stabilizer is from 20:1 to 150:1.
 - 64. An oxygenating additive as claimed in claim 63, wherein the ratio of the combined amounts of the compounds of general formulae (III) and (IV) to the stabilizer is from 75:1 to 125:1.
 - 65. An oxygenating additive for a hydrocarbon fuel comprising a first and a second compound, both the first and the second compounds having the general formula (I):

25

$$R_2 - O - (CO) - R_1$$
 (I)

wherein R₁ in each of the first and the second compound is independently selected from hydrogen, lower alkyl, lower alkenyl and lower alkynyl groups; and



R₂ in each of the first and second compound is independently selected from lower alkyl, lower alkenyl and lower alkynyl groups.

- 66. An oxygenating additive as claimed in claim 65, wherein R₁ and R₂ in each of the first and second compounds are both independently selected from hydrogen, and lower alkyl groups.
 - 67. An oxygenating additive as claimed in claim 66, wherein the first compound is methyl acetate and the second compound is ethyl acetate.
 - 68. An oxygenating additive as claimed in claim 67, wherein methyl acetate and ethyl acetate are present in a ratio of from 1:2 to 2:1.
 - 69. An oxygenating additive as claimed in claim 68, wherein methyl acetate and ethyl acetate are present in a ratio of 1:1.

15